

6. ダクタイル鑄鉄異形管の管厚、外径、フランジ突部質量

呼び径	管厚 (mm)		外径 (mm)	フランジ			
	T			7.5K		10K	
	G X形	G X形以外	D ₂	R F形	G F形	R F形	G F形
75	8.0	8.5	93.0	3.77	3.66	2.28	2.17
100	8.0	8.5	118.0	4.55	4.40	2.75	2.61
150	8.5	9.0	169.0	6.22	6.02	5.59	5.39
200	9.5	11.0	220.0	8.06	7.80	6.75	6.49
250	10.5	12.0	271.6	11.5	11.1	10.7	10.4
300	10.5	12.5	322.8	14.2	13.8	11.4	11.0
350	11.0	13.0	374.0	18.8	18.3	13.4	12.9
400	12.0	14.0	425.6	21.8	21.3	19.4	18.9
450	—	14.5	476.8	28.3	27.7	24.7	24.1
500	—	15.0	528.0	32.0	31.4	28.3	27.6
600	—	16.0	630.8	38.9	38.2	39.0	38.3
700	—	17.0	733.0	49.9	49.1	52.1	51.3
800	—	18.0	836.0	66.1	65.1	67.7	66.7
900	—	19.0	939.0	85.3	84.3	80.3	79.2
1000	—	20.0	1041.0	101	98.2	100	97.2
1100	—	21.0	1144.0	120	116	122	119
1200	—	22.0	1246.0	140	136	152	148
1350	—	24.0	1400.0	181	177	194	190
1500	—	26.0	1554.0	216	212	239	235
1600	—	27.5	1650.0	275	264	295	284
1650	—	28.0	1701.0	286	275	308	296
1800	—	30.0	1848.0	318	306	358	345
2000	—	32.0	2061.0	360	346	421	408
2100	—	33.0	2164.0	386	372	461	447
2200	—	34.0	2280.0	424	409	494	479
2400	—	36.0	2458.0	538	522	651	634
2600	—	37.5	2684.0	549	525	683	659

編集注記 呼び径 50 は、定形寸法以外の製品に適用しないため記載していない。

及び直部 1 m 当たりの質量

単位 kg

突部				直部 1 m	
16K		20K		G X形	G X形以外
R F形	G F形	R F形	G F形		
3.00	2.89	3.29	3.18	15.274	16.134
3.98	3.84	4.33	4.18	19.767	20.907
7.73	7.53	8.90	8.70	30.644	32.346
9.89	9.63	11.2	11.0	44.919	51.641
16.5	16.2	19.6	19.3	61.582	69.975
19.7	19.3	23.1	22.7	73.658	87.126
26.0	25.6	30.0	29.5	89.692	105.416
36.0	35.5	42.8	42.3	111.485	129.437
47.3	46.7	55.5	54.9	—	150.573
56.3	55.7	65.4	64.8	—	172.848
75.0	74.2	86.1	85.3	—	220.958
98.2	97.4	143	142	—	273.412
132	131	213	212	—	330.736
156	155	256	255	—	392.643
207	204	—	—	—	458.682
237	234	—	—	—	529.730
287	283	—	—	—	604.867
369	365	—	—	—	741.798
451	446	—	—	—	892.386
—	—	—	—	—	1002.244
—	—	—	—	—	1052.228
—	—	—	—	—	1225.099
—	—	—	—	—	1458.438
—	—	—	—	—	1579.622
—	—	—	—	—	1715.318
—	—	—	—	—	1958.540
—	—	—	—	—	2229.252